

CONDUITS ALU

ALU : Conduit en aluminium simple paroi, du Ø 80 au Ø 200 : épaisseur 0,55mm, du Ø 250 au Ø 500 : épaisseur 1mm.



	ELEMENTS DROITS			DEVIATION			INSPECTION & NETTOYAGE	
Ref. Commande	F001	F002	F004	F003	F006	F005	F007	F007B
Libellé	Élément 1000 mm	Element 500 mm	Coude 90°	Coude 45°	Té 90°	Té 135°	Tampon	Tampon purge
80	8,49	5,48	5,03	-	10,23	24,82	6,02	6,88
90	8,74	5,63	5,43	4,47	10,63	24,82	6,02	7,05
100	9,09	5,84	6,02	4,97	10,76	26,33	6,26	7,05
110	12,34	7,8	6,63	5,48	12,76	27,12	6,65	7,61
130	14	8,49	8,01	6,56	13,46	27,12	7,27	8,57
150	15,56	9,62	9,98	8,16	15,75	28,63	9,22	9,18
180	18,89	11,48	12,12	9,81	23,32	38,02	10,97	10,48
200	20,18	12,76	14,45	11,93	26,04	46,54	11,05	11,31
250	33,5	22,13	38,73	30,83	48,06	79,82	11,81	22,27
300	39,75	25,88	55,56	44,53	94,16	106,39	12,48	33,13
350	52,26	28,85	71,86	57,52	118,08	172,92	13,08	53,2
400	73,31	43,59	95,48	76,42	139,28	175,33	14,04	76,22
450	78,71	50,84	-	90,51	153,71	182,53	-	-
500	82,26	54,58	-	93,39	-	-	-	-
Ref. Emballage	02TUYAGA-LU002	02TUYAGA-LU001	02COU90A-LU014	02COU45A-LU014	02TE090A-LU001	02TE135A-LU007	02TAMPOA-LU001	02PURGEA-LU001



	TERMINAUX		FIXATIONS
Ref. Commande	F008	F009	F010
Libellé	Chapeau tréga alu	Rosace	Collier crampon
80	26,22	4,59	4,4
90	28,48	4,64	4,42
100	30,96	4,83	4,62
110	33,6	4,88	4,67
130	38,84	5,15	4,88
150	43,04	5,28	5,03
180	55,11	5,57	5,27
200	68,21	6,48	5,43
250	154,8	7,2	5,84
300	186,42	8,12	-
350	279,97	9,08	-
400	-	-	-
450	-	-	-
500	-	-	-

Ref. Emballage 02CHAPTALU001 02ROSACALU001 02COLLIGAL001



RÉDUCTIONS ALU

RÉDUCTIONS ALU			
Ref. cde.	Diamètre	€	Ref. emb.
AB			
FR 080 A 080	80M > 80F	15,61	
FR 080 A 090	80M > 90F	15,61	09REDHSALU120
FR 080 A 100	80M > 100F	15,61	03REDHSALU003
FR 080 A 110	80M > 110F	15,61	03REDHSALU122
FR 080 A 130	80M > 130F	15,61	02REDHSALU001
FR 090 A 100	90M > 100F	15,61	03REDHSALU008
FR 090 A 110	90M > 110F	15,61	02REDHSALU007
FR 090 A 125	90M > 125F	15,61	02REDHSALU010
FR 090 A 130	90M > 130F	15,61	03REDHSALU011
FR 100 A 110	100M > 110F	15,61	02REDHSALU016
FR 100 A 130	100M > 130F	15,61	02REDHSALU021
FR 110 A 130	110M > 130F	16,52	03REDHSALU026
FR 110 A 150	110M > 150F	19,52	02REDHSALU033
FR 120 A 130	120M > 130F	15,98	-
FR 125 A 130	125M > 130F	15,98	02REDHSALU047
FR 125 A 153	125M > 153F	19,52	02REDHSALU050
FR 130 A 150	130M > 150F	19,52	03REDHSALU054
FR 130 A 153	130M > 153F	19,52	02REDHSALU059
FR 130 A 180	130M > 180F	19,52	03REDHSALU055
FR 130 A 200	130M > 200F	30,75	03REDHSALU056
FR 150 A 180	150M > 180F	19,52	03REDHSALU070
FR 150 A 200	150M > 200F	30,75	03REDHSALU071
FR 180 A 200	180M > 200F	30,75	02REDHSALU087
FR 200 A 250	200M > 250F	42,2	03REDHSALU095
FR 250 A 300	250M > 300F	46,06	03REDHSALU111
FR 350 A 400	350M > 400F	75,92	02REDHSALU117

RÉDUCTIONS ALU			
Ref. cde.	Diamètre	€	Ref. emb.
CD			
FR 110 A 100	110M > 100F	15,61	02REDHSALU016



ALU FLEX

Nom approprié pour l'évacuation des fumées, à utiliser exclusivement pour l'évacuation d'air.

Particulièrement adapté pour le raccordement d'appareils électroménagers et pour les aérations diverses. Épaisseurs: 0,12mm

Ref. Commande	ELEMENTS DROITS		CONNECTIONS
	A30	A30B	A31
Libellé	Flexible alu sans film 3 m	Flexible alu + film 3 m	Raccord flexible alu
80	10,37	11,59	3,19
100	11,69	13,02	3,51
110	13,22	14,55	3,93
120	13,7	15,04	4,13
125	14,65	15,97	4,25
140	15,78	17,22	4,7
150	16,35	17,79	4,95
160	18,48	19,81	7,2
200	23,26	-	9,5
Ref. Emballage	03ALUFLALU004	03ALUFLALU003	03RRACCOALU001